

# -GENESIS-

## General Purpose Security & Control Cable

Part Number: 1260

### 22/1 Pair Shielded Low Cap. + 12/2 + 18/1

**Ratings** CM, CL2, Sunlight Resistant

**Approvals** ETL Listed

<b>Construction</b>	<b>22/1pr Shielded</b>	<b>12/2 Stranded</b>	<b>18/1 Stranded</b>
Conductor	22 AWG 7 Strand Bare Copper	12 AWG 65 Strand Bare Copper	18 AWG 19 Strand Bare Copper
Conductor Count	2 (1-pair)	2	1
Insulation	Polypropylene (0.024")	Polypropylene (0.010")	Polypropylene (0.006")
Insulation Colors	Purple, White	Black, Red	Orange
Shielding	Aluminum Foil/Mylar w/ Tinned-Copper Drain	N/A	N/A

Rip Cord Yes

Jacket PVC (0.045 " nom.)

Overall Diameter 0.350" nom.

Print Legend GENESIS P/N 1260 1C18 + 2C12 (POWER)+1PR22 SHIELDED (DATA) (ETL) 3038058 CL2  
OR CM SUNRES (RoHS) W/O#XXXXX-XXX- XXXXX FT RM# A B C D E F 1 2 3 4 5 6 7 8

<b>Properties</b>	<b>22/1pr Shielded</b>	<b>12/2 Stranded</b>
Operating Voltage	300 Volts max.	300 Volts max.
DC Resistance	16.9 Ohms/1000' at 20°C	2.5 Ohms/1000' at 20°C
Capacitance	13.0 pF/ft. nom.	23.0 pF/ft. nom.
Impedance	115 Ohms nom.	90 Ohms nom.

Temperature -20°C to 60°C

Flame Rating UL 1685 Vertical Tray

RoHS Compliant Yes

Country of Origin USA