

-GENESIS-

Riser Rated Security & Control Cable Part Number: 2209

22 AWG 12 Stranded Conductors Shielded

Ratings CMR, CL3R, FPLR, FT4, Sunlight Resistant
Approvals ETL Listed

Construction

Conductor 22 AWG 7 Strand Bare Copper
Conductor Count 12
Insulation Polypropylene (0.006" nom.)
Insulation Colors Black, Red, White, Green, Brown, Blue, Orange, Yellow, Purple, Gray, Pink, Tan
Lay Length 3.50" nom.
Shielding Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain
Rip Cord Yes
Jacket PVC (0.017 " nom.)
Overall Diameter 0.210" nom.
Print Legend GENESIS P/N 2209 12C 22AWG SHIELDED 3038058 (ETL) CL3R OR FPLR OR CMR
C(ETL)US FT4 SUN RES 75C (RoHS) W/O# XXXXXX-XXXXXXX XXXXFT A B C D E F 1
2 3 4 5 6 7 8 9

Properties

Operating Voltage 300 Volts max.
DC Resistance 16.9 Ohms/1000' at 20°C
Capacitance 18.5 pF/ft. nom.
Impedance 59 Ohms nom.

Temperature -20°C to 75°C
Flame Rating UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)
RoHS Compliant Yes

Country of Origin USA