

-GENESIS-

Riser Rated Security & Control Cable Part Number: 2228

18 AWG 3 Stranded Conductors Shielded

Ratings CMR, CL3R, FPLR, FT4, Sunlight Resistant
Approvals ETL Listed

Construction

Conductor 18 AWG 19 Strand Bare Copper
Conductor Count 3
Insulation Polypropylene (0.006" nom.)
Insulation Colors Black, Red, White
Lay Length 3.25" nom.
Shielding Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain
Rip Cord Yes
Jacket PVC (0.015" nom.)
Overall Diameter 0.161" nom.
Print Legend GENESIS P/N 2228 3C18 SHIELDED 3038058 (ETL) CL3R OR FPLR OR CMR C(ETL)US FT4
SUN RES 75C (RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3
4 5 6 7 8 9

Properties

Operating Voltage 300 Volts max.
DC Resistance 6.66 Ohms/1000' at 20°C
Capacitance 36.3 pF/ft. nom.
Impedance 41 Ohms nom.

Temperature -20°C to 75 °C
Flame Rating UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)
RoHS Compliant Yes

Country of Origin USA