



## GENESIS SERIES

### Low Voltage Cable Part No. 1108

Description: 22 AWG 8/C Sol CM-CL2  
Specifications: UL Standards 13, & 444; NEC Articles 725 & 800

#### Construction:

Conductor 22 AWG Solid Bare Copper  
Insulation Polypropylene  
Insulation Thickness 0.006" nom.  
Insulation Colors Blk,Wht,Red,Grn,Blu,Brn,Orn,Ylw  
Insulation Diameter 0.036 nom.  
Lay Length 2.25" nom.

Jacket PVC  
Jacket Thickness 0.015" nom.  
Outside Diameter 0.152" nom.  
Legend (Ink Print) **HONEYWELL P/N 1108 8C22 3038058 (ETL) CL2 OR CM C(ETL)US SUN RES (RoHS)  
W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9**

#### Properties

Temperature Rating -20 to 60 °C  
Operating Voltage 300 Volts max.  
Capacitance 15 pf/ft nom.  
Impedance 100 Ohms nom.  
DC Resistance 17.5 Ohms/M' at 20°C  
Flame Rating UL 1685 Vertical Tray