

Description: 22 AWG 4/C STR OAS CM-CL2  
Specifications: UL Standards 13, & 444; NEC Article 725

**Construction:**

Conductor 22 AWG 7/0.0096 Stranded Bare Copper  
Insulation Polypropylene  
Insulation Thickness 0.006" nom.  
Insulation Colors Blk,Red,Wht,Grn  
Insulation Diameter 0.042 nom.  
Lay Length 1.5" nom.  
Drain Wire 22 AWG 7/0.0096" Tinned Copper  
Shield 0.001" Thick Aluminum/Mylar

Jacket PVC  
Jacket Thickness 0.015" nom.  
Outside Diameter 0.139" nom.  
Legend (Ink Print)

**HONEYWELL 22 AWG 4/C (ETL) TYPE CM-CL2 - Sun. Res.(RoHS) - 3038058  
W/O# XXXXXX-XXX XXXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9**

**Properties**

Temperature Rating -20 to 60 °C  
Operating Voltage 300 Volts max.  
Capacitance 28 pf/ft nom.  
Impedance 53 Ohms nom.  
DC Resistance 16.5 Ohms/M' at 20°C  
Flame Rating UL 1581 Vertical Tray