

Description: 20 AWG 2/C STR OAS CM-CL2  
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800

**Construction:**

Conductor 20 AWG 7/28 Stranded Bare Copper  
Insulation Polypropylene  
Insulation Thickness 0.006" nom.  
Insulation Colors Blk,Red  
Insulation Diameter 0.051 nom.  
Lay Length 2.0" nom.  
Drain Wire 24 AWG 7/32 Tinned Copper  
Shield .001" Thick Aluminum/Mylar

Jacket PVC  
Jacket Thickness 0.015" nom.  
Outside Diameter 0.138" nom.  
Legend (Ink Print) **HONEYWELL P/N 1212 2C22 SHIELDED 3038058 (ETL) CL2 OR CM C(ETL)US  
SUN RES (RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E  
F 1 2 3 4 5 6 7 8 9**

**Properties**

Temperature Rating -20 to 60 °C  
Operating Voltage 300 Volts max.  
Capacitance 33 pf/ft nom.  
Impedance 45 Ohms nom.  
DC Resistance 10.5 Ohms/M' at 20°C  
Flame Rating UL 1685 Vertical Tray