

Description: 14 AWG 3/C Stranded OAS CM-CL2  
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800

**Construction:**

Conductor 14 AWG 19/0.0147 Bare Copper  
Insulation Polypropylene  
Insulation Thickness 0.007" nom.  
Insulation Colors Blk, Red, Wht  
Insulation Diameter 0.089 nom.  
Lay Length 3.75" nom.  
Drain Wire 18 AWG 16/30 Tinned Copper  
Shield 0.001" Thick Aluminum/Mylar

Jacket PVC  
Jacket Thickness 0.016" nom.  
Outside Diameter 0.222" nom.  
Legend (Ink Print) HONEYWELL P/N 1230 3C14 SHIELDED 3038058 (ETL) CL2 OR CM C(ETL)US  
SUN RES (RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E  
F 1 2 3 4 5 6 7 8 9

**Properties**

Temperature Rating -20 to 60 °C  
Operating Voltage 300 Volts max.  
Capacitance 43 pf/ft nom.  
Impedance 45 Ohms nom.  
DC Resistance 2.53 Ohms/M' at 20°C  
Flame Rating UL 1685 Vertical Tray