

Description: 22 AWG 2Pr Str OAS CM-CL2
Specifications: UL Standards 13, & 444; NEC Article 725
Assembly: Tubed jacket over, twisted, cabled, overall shielded pairs

Construction:

Conductor: 22 AWG 7/30 Bare Copper
Insulation: Polypropylene
Insulation Thickness: 0.006" nom.
Insulation Colors: Pairs - Blk/Red, Blk/Wht
Insulation Diameter: 0.042" nom.
Lay Length: 1.5" nom.(pair), 3.0" nom.(cable)
Drain Wire: 22 AWG 7/30 Tinned Copper
Shield: .001" Thick Aluminum/Mylar

Jacket: PVC
Jacket Thickness: 0.015" nom.
Outside Diameter: 0.181" nom.
Legend (Ink Print): HONEYWELL 22 AWG 2/PR (ETL) TYPE CM-CL2 - Sun. Res. (RoHS)- 3038058
W/O# XXXXXX-XXX XXXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Temperature Rating: -20 to 60 °C
Operating Voltage: 300 Volts max.
Capacitance: 30 pf/ft nom.
Impedance: 50 Ohms nom.
DC Resistance: 16.5 Ohms/M' at 20°C
Flame Rating: UL Vertical Tray