

Description: 22 AWG 2/C Stranded OAS CMR-CL2R-FT4  
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800

#### Construction:

Conductor 22 7/.0096 Bare Copper  
Insulation Polypropylene  
Insulation Thickness 0.006" nom.  
Insulation Colors Blk,Red  
Insulation Diameter 0.042" nom.  
Lay Length (Twist) 1.75" nom.  
Drain Wire 24 7/32 Tinned-Copper  
Shield Alum/Mylar tape

Jacket PVC  
Jacket Color 0.015" nom.  
Jacket Thickness 0.015" nom.  
Outside Diameter 0.114" nom.  
Legend (Ink Print) HONEYWELL P/N 2202 2C22 SHIELDED 3038058 (ETL) CL2R OR CMR C(ETL)US FT4  
SUN RES (RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3  
4 5 6 7 8 9

#### Properties:

Temperature Rating -20 to 60 °C  
Operating Voltage 300 Volts max.  
Capacitance 45 pf/ft nom.  
Impedance 40 Ohms nom.  
DC Resistance 16.5 Ohms/M' at 20°C  
Flame Rating UL 1666 (Riser), CSA FT4