

Description: 16 AWG 4/C Stranded OAS CMR-CL2R-FT4  
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800

**Construction:**

Conductor 16 26/30 Bare Copper  
Insulation Polypropylene  
Insulation Thickness 0.006" nom.  
Insulation Colors Blk,Red,Wht,Grn  
Insulation Diameter 0.070" nom.  
Lay Length (Twist) 2.75" nom.  
Drain Wire 20 7/28 Tinned-Copper  
Shield Alum/Mylar tape

Jacket PVC  
Jacket Thickness 0.015" nom.  
Outside Diameter 0.204" nom.

Legend (Ink Print) **HONEYWELL P/N 2222 4C16 SHIELDED 3038058 (ETL) CL2R OR CMR C(ETL)US FT4  
SUN RES (RoHS) C(ETL) FT4 W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B  
C D E F 1 2 3 4 5 6 7 8 9**

**Properties**

Temperature Rating -20 to 60 °C  
Operating Voltage 300 Volts max.  
Capacitance 40 pf/ft nom.  
Impedance 40 Ohms nom.  
DC Resistance 4.15 Ohms/M' at 20°C  
Flame Rating UL 1666 (Riser), CSA FT4