

Description: 14 AWG 4/C Stranded OAS CMR-CL2R-FT4
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800

Construction:

Conductor 14 19/.0147 Bare Copper
Insulation Polypropylene
Insulation Thickness 0.008" nom.
Insulation Colors Blk,Red,Wht,Grn
Insulation Diameter 0.089" nom.
Lay Length (Twist) 4.25" nom.
Drain Wire 18 16/30 Tinned-Copper
Shield Alum/Mylar tape

Jacket PVC
Jacket Thickness 0.016" nom.
Outside Diameter 0.252" nom.
Legend (Ink Print) **HONEYWELL P/N 2224 4C14 SHIELDED 3038058 (ETL) CL2R OR CMR C(ETL)US FT4
SUN RES (RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3
4 5 6 7 8 9**

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 41 pf/ft nom.
Impedance 37 Ohms nom.
DC Resistance 2.60 Ohms/M' at 20°C
Flame Rating UL 1666 (Riser), CSA FT4