

Description: 22 AWG 2Pr STR OAS CMR-CL2R
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800

Construction:

Conductor 22 AWG 7/30 Bare Copper
Insulation Polypropylene
Insulation Thickness 0.006" nom.
Insulation Colors Pairs - Blk/Red, Blk/Wht
Insulation Diameter 0.042" nom.
Lay Length 1.5" nom.(pair), 3.0" nom.(cable)
Drain Wire 24 AWG 7/32 Tinned Copper
Shield .001" Thick Aluminum/Mylar

Jacket PVC
Jacket Color Gray
Jacket Thickness 0.015" nom.
Outside Diameter 0.181" nom.
Legend (Ink Print) **HONEYWELL P/N 2281 2PR22 SHIELDED 3038058 (ETL) CL2R OR CMR C(ETL)US FT4 SUN RES (RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 99**

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 30 pf/ft nom.
Impedance 50 Ohms nom.
DC Resistance 16.5 Ohms/M' at 20°C
Flame Rating UL 1666 (Riser), CSA FT4