



**GENESIS SERIES CABLE**

**Power Limited Fire Alarm Cable  
Part No. 4208**

Description: 14 AWG 2/C Shielded FPL  
Compliance: UL Standard 1424; NEC Article 760

**Construction:**

Conductor 14 AWG Solid Bare Copper  
No. of Conductors 2  
Assembly Tubed jacket over twisted and shielded insulated conductors

Insulation

Type Polypropylene  
Color Blk, Red  
Thickness 0.006" nom.  
Diameter 0.076" nom"  
Lay Length 2.5" nom.  
Drain Wire 18 Solid Tinned-Copper  
Shield 0.001" thick Aluminum/Mylar

Jacket

Type PVC  
Color Red  
Thickness 0.015" nom.  
Diameter 0.186" nom.  
Legend (Ink Print) HONEYWELL 14 AWG 2/C (ETL) FPL/CL2 3038058 SUN RES (RoHS) W/O # XXXXXX-XXX  
XXXXFT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

**Properties**

Temperature Rating -20 to 75 °C  
Operating Voltage 300 Volts max.  
Capacitance 52 pf/ft nom.  
Impedance 29 Ohms nom.  
DC Resistance 2.54 Ohms/M' at 20°C  
Flame Rating UL Vertical Tray