

Description: 20 AWG RG59/U COAX + 18/2 CL2
 Compliance: UL13 & 444, NEC Article 820

Construction:

Conductors 20 AWG Solid Bare Copper center conductor
 2 x 18AWG 19/.0092 Stranded Bare Copper

Insulation

Type Foamed Poly
 Color White
 Thickness 0.057" nom.
 Diameter 0.145" nom

Insulated

Conductors
 Polypropylene
 Blk,Red
 0.006" nom.
 0.058" nom

Braid
 Strands 0.0063" nom. Bare Copper
 % Coverage 95 nom.

Jacket

Type PVC
 Color White
 Thickness 0.020" nom.
 Diameter 0.395 x 0.285" nom.

Coax

0.034" nom
 0.242" nom.

Legend (Ink Print)

**HONEYWELL P/N 5009 CCTV PREMIUM RG 59/U 20 AWG + 18/2 3038058 (ETL) CL2
 75C SUN RES (RoHS) W/O# XXXXXX-XXX XXXX FT CAMERA/ZONE A B C D E F 1 2 3 4
 5 6 7 8 9**

Properties

Temperature Rating -20 to 75 °C
 Capacitance 17 pf/ft nom.
 Impedance 75 Ohms nom.
 Resistance (Conductor) 10.9 Ohms/M' at 20°C
 Resistance (Shield) 2.6 Ohms/M' at 20°C
 Attenuation (db/100') 0.2 at 1 MHz, 5.9 at 400 MHz, 10.8 at 1000 MHZ
 Flame Rating UL 1685 Vertical Tray

