

Description: 16 AWG 4/C AUDACIOUS HTS CMR-CL3R FT4 w/Ripcord  
Specifications: UL Standards 13, & 444; NEC Articles 725 & 800

#### Construction:

Conductor 16 AWG 65/34 Stranded OFBC  
Insulation PVC  
Insulation Thickness 0.015" nom.  
Insulation Colors Blk,Red,Wht,Grn  
Insulation Diameter 0.086 nom.  
Lay Length 4.0" nom.

Jacket PVC  
Jacket Color Purple or White  
Jacket Thickness 0.035" nom.  
Outside Diameter 0.294" nom.

HONEYWELL AUDACIOUS OXYGEN FREE P/N 5474 4C16 E175106 (UL) CL3R OR CMR  
C(UL)US FT4 75C SUN RES (RoHS) W/O#XXXXXX-XXXXXX XXXXX FT - L C R LR RR  
Legend (Ink Print) RM# A B C D E F 1 2 3 4 5 6 7 8 9 (PAT PEND)

#### Properties

Temperature Rating -20 to 60 °C  
Operating Voltage 300 Volts max.  
Capacitance 22 pf/ft nom.  
Impedance 85 Ohms nom.  
DC Resistance 4.19 Ohms/M' at 20°C  
Flame Rating UL 1666 Riser