

## T50MR0M4



**Article Number:** 113-05002

**Screw Mount Tie, 50 lb 8.5" Long, Max Bundle Diameter 1.8", #10 Screw, PA66HS, Black, 1,000/pkg**



### Base Data

**Local Order Number** T50MR0M4

**Type** T50MR

**Color** Black (BK)

**Features and Benefits**

- Mount design secures firmly with any #10 Screw.
- Screw mount style creates low insertion and high extraction force.

**Product Description** Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.

**Fixation Method (FF)** fixing hole

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Screw Mount Tie, 50 lb 8.5" Long, Max Bundle Diameter 1.8", #10 Screw, PA66HS, Black, 1,000/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 50.0 lbs

**Minimum Tensile Strength (N)** 225 N

**Length L (imperial)** 8.5 "

**Length L (metric)** 215.0 mm

**Width W (imperial)** 0.18 "

**Width W (metric)** 4.7 mm

**Height H (imperial)** 0.22 "

**Height H (metric)** 5.7 mm

**Bundle Diameter min (imperial)** 0.06 "

**Bundle Diameter min (metric)** 1.5 mm

**Bundle Diameter max (imperial)** 1.8 "

**Bundle Diameter max (metric)** 45.0 mm

**Mounting Hole Diameter D (imperial)** 0.21 "

**Mounting Hole Diameter D (metric)** 5.4 mm

**Thickness T (imperial)** 0.05 "

**Thickness T (Metric)** 1.2 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 1000

Carton Quantity 5000

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>CSA Certified</b>	No
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +221 °F (-40 °C to +105 °C)
<b>ROHS Conformity</b>	Yes
<b>Certification / Specification</b>	UL
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes