

**Part #: DX006**

**6 CHANNEL  
D-Series Distribution Outside Plant Cables**

Laser Ultra-Fox™ Fiber Performance	
Industry Standard Designation	Maximum Cabled Attenuation (dB/km)
Core/Cladding Diameter (µm)	Minimum Laser EMB Bandwidth (MHz-km)
Numeric Aperture	Minimum OFL LED Bandwidth (MHz-km)
Proof Test Level (kpsi)	100


Installation and Operating Characteristics		
	Installation	Operating
Max Tensile Load	2,670 N (600 lbs)	890 N (200 lbs)
Min Bend Radius	12.6 cm (5.0 in)	6.3 cm (2.5 in)

Mechanical and Environmental	
Impact Resistance EIA/TIA-455-25A	1,000 Impacts
Crush Resistance TIA/EIA-455-41A	1,500 N/cm
Flex Resistance	1,000 cycles
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +85°C
Installation Temperature (actual temp. of cable)	-30°C to +60°C

Cable Characteristics	
Jacket Color	
Jacket Material	
Buffer Material	Hard Elastomeric
Cable Weight	29 kg/km (20 lbs/1000')
Cable Diameter	6.3 mm ( 0.25 in)

6 CHANNEL  
D-Series Distribution Outside Plant Cables

Part #: DX006



#### Standards

OCC's outside plant tight-buffered fiber optic cables meet the functional requirements of the following standards:

- ICEA-S-87-640
- TIA-568
- TIA-598

#### Applications:

- Outdoor distribution cable for duct or aerial lash installations along utility poles for cable television, telecom or other outside plant campus backbone applications

#### Features:

- Tight-buffered construction for easy, direct connector termination or splicing
- Polyethylene outer cable jacket for excellent UV and weather resistance
- High performance tight-buffer on the optical fibers for excellent environmental and mechanical protection
- Wide operating temperature of -40°C to +85°C
- 900µm buffer eliminates the need for costly and time-consuming installation of fan-out kits or pig-tail splices because connectors terminate directly to the fiber
- All-dielectric design does not require grounding or bonding